

TF S40B

Published: 2006-04-05

Drawing No: 404080/C

POS	DESCRIPTION	PART	QTY	COMMENTS
1	Frame TF10B	100359	1	
2	Top Bracket 10 EC05	100423	1	
3	Yoke Attachment	300547K	2	
4	Cylinderaxle $\varnothing 30$	404276	1	Replacing 400119
5	Lockcylinder EC05 E.L	300783	1	
6	Indicating Stick	401001	1	L=247
7	Spacer (small)	400127	1	
8	Bushing 40/44x30	630307	2	WB 702
9	Locking Wedge	302617	2	
10	Locating Pin	400611	2	
11	Locking Axle	400565	1	
12	Spring	640102	2	32x178
13	Hex Head Screw 6 x 16	610109	1	8.8 Zinc plated ISO 4017
14	Hex. Nut M6 Nylon Lock	610921	1	DIN 985
15	Flat head socket screw 10x30	610635	2	10.9 Untreated DIN 7991
16	Axle $\varnothing 40$ TF10	300785	1	
17	Washer TF10B	400617	2	
18	Hex Head Screw 8 x 25	610124	1	8.8 Yellow chromated ISO 4014
19	Tiltcylinder	400552	1	
20	Socket Head Screw 16 x 30	610518	2	12.9 Untreated ISO 4762
21	Socket Head Screw 12 x 20	610472	1	12.9 Untreated ISO 4762
22	Socket Head Screw 12 x 90	610486	4	12.9 Untreated ISO 4762
23	Grease Nipple	711403	2	R1/8" Straight

Complete componentdrawing for:
 Tiltcylinder 400552 (pos. 19): **404954**
 Lockcylinder 300783 (pos. 5): **404959**

